



PoE-Texas LLC
 3616 Far West Blvd
 Austin Tx 78731
 512-479-0317

<http://poe-texas.com>

WS-POE-8-48v Power injector for 8x 802.3af or 48v devices
 add power to any non-PoE switch



VOIP phones, cameras and WiFi AP's need from 3 to 15 watts each, with this injector, you can provide remote power up to 328 ft from the power source. If your device data sheet shows "48v 350ma" please understand that this is not the power your device needs, but the max power that is available according to the 802.3af spec. For example, a Polycom VOIP phone is 802.3af compatible, but needs about 4.5 watts to operate. Therefore, one 8 port injector and a 60watt power supply can power 8 phones at low cost. Use with any 10/100 switch. For gigabit, see our other devices.

If the device shows "12v, PoE" on the data sheet – this usually means that the device uses 12v when powered from a transformer – and 48v when powered via CAT-5. We can answer your questions if you are not sure.

- 8 Port Injector – 8 LAN and 8 POE ports
- 100-240v 50/60 hz AC input UL / CE / FCC
- 60watt and 120watt versions
- 10/100 operation – see WT-GPOE for 10/100/1000
- Use with any Ethernet switch
- Ideal for WiFi, VOIP phone, IP Cameras
- Technical support from Austin
- Online copper line loss [calculator](#)
- US power cord
- Includes reversing cable for Cisco 7940/7960

PIN	LAN	POE
1	Data	Data
2	Data	Data
3	Data	Data
4	N.C.	+Volt
5	N.C.	+Volt
6	Data	Data
7	N.C.	GND
8	N.C.	GND

INPUT: 9-56 volts DC 
 See manuals at <http://wifi-texas.com/pdf>

Order information: WS-POE-8-48v60w 48 volts, 60 watts
 WS-POE-8-48v120w 48 volts, 120 watts