

Multi Port Passive POE injector


PoE-Texas LLC 3616 Far West Blvd Austin Tx 78731 512-479-0317

http://poe-texas.com

WT-GPOE-8 for 802.3af or passive 802.3at mode A power for 8 gigabit devices









- WiFi-Texas Brand Injectors
- 8 Port Gigabit Ethernet Injector
 - 8 Shielded RJ-45 LAN
 - 8 Shielded RJ-45 LAN+POE
 - 10/100/1000 data rates
- Injector: 180 mm x 45mm x 25mm including 2x 10mm tabs
- wall mount stackable
- 650 ma automatic resettable fuse on each port
- Same voltage to all ports power is shared as needed by the devices
- Use with any Ethernet switch
 - PoE or non-PoE switches
- Standard power connector
 - 2.1mm x 5.5mm
- Additional Phoenix DC connector
 - 3.5mm model 1844236
 - pin 2 (minus) 3 (plus)
- LED status indicator
- Operating Temperature
 - -0 to 65 deg C
- Mode A operation
 - pins 1-2 (-)
 - pins 3-6 (+)
 - reversing cable available
- Ideal for IP Cameras, VOIP phone, WiFi Access Points
- Technical support from Austin
- Select the power supply you need 48 or 56 volts
- Power is always on
 - no auto-negotiation
 - powers 802.3af / 802.3at devices "passively"
- Use our reversing jumper for reverse polarity if needed (WS-Cisco)

power input

Device Spec	Mode A - DC Input RJ45 pins 1,2- 3,6+	Note
Passive 802.3at	56 volts 120 watts	Please see WT-AT-8 for active PoE
802.3af or "12v, PoE"	48 volts 60 or 120 watts	IP Phones need about 5w each Other devices up to 15w each

(sometimes misspelled as WS-GPOE-8)